

## CLAIMS

What is claimed is:

1. In a computer system having a display device, the display device having a plurality of pixels each having a plurality of pixel sub-components of different colors, a method of adjusting image data to a grid defined by the pixels and pixel sub-components in preparation for rasterizing an image on the display device, the method comprising:

obtaining image data having selected elements with positions relative to the grid, the positions of at least one of the selected elements of the obtained image data not coinciding with a boundary between pixel sub-components;

hinting the image data such that a typographical feature defined by one or more of the selected elements is adjusted to a position on the grid that corresponds to a selected boundary between pixel sub-components, the selected boundary being designated as a high contrast boundary due to the color contrast of the sub-pixel components which define the boundary, and which may comprise a boundary other than one which is between pixels; and

displaying the image on the display device using the image data, the typographical feature being displayed at the high contrast boundary.

2. A method as defined in claim 1, wherein the image data represents a character, the method further comprising analyzing the topology of the character at runtime to identify the typographical feature that is to be adjusted.

3. A method as defined in claim 1, wherein the image is displayed such that individual pixel sub-components of the pixels represent spatially different portions of the image

data rather than the different portions being represented by entire pixels that include the individual pixel sub-components.

4 4. A method as defined in claim 1, wherein the typographical feature is a stem of a character represented by the image data.

5 5. A method as defined in claim 4, wherein hinting the image data is conducted such that a left edge of the stem is aligned with the high contrast boundary.

6 6. A method as defined in claim 1, wherein the typographical feature is a horizontal segment of a character represented by the image data.

7 7. A method as defined in claim 1, wherein hinting the image data comprises:  
grid fitting the image data to grid points of the grid that corresponds to the pixels and pixel sub-components of the display device such that the one or more elements defining the typographical feature of the image data correspond to the grid points;  
phase adjusting the typographical feature such that the typographical feature coincides with the high contrast boundary; and  
interpolating the image data such that the position on the grid of remaining elements of the image data is adjusted.

10 8. A method as defined in claim 7, wherein the image data represents a character to be displayed on the display device, the method further comprising analyzing the topology of the character at runtime to identify the typographical feature.

11 9. A method as defined in claim 7, wherein phase adjusting further comprises:  
analyzing hinting instructions associated with the image data for patterns that  
are indicative of the typographical feature;

deriving, from the hinting instructions, a directed acyclic graph, wherein the  
topology of the typographical feature is at least partially defined by one or more nodes  
of the directed acyclic graph; and

based on a traversal of the directed acyclic graph, identifying the position of  
the typographical feature and repositioning the typographical feature to the high  
contrast boundary.

12 10. A method as recited in claim 9, further comprising:  
traversing the directed acyclic graph; and  
encountering a node that corresponds to a point of the image data that is to be  
repositioned on the grid; and

accounting for an error introduced by a repositioning of a point corresponding  
to a previous node of the directed acyclic graph.

13 11. A method as defined in claim 9, wherein analyzing the hinting instructions  
further comprises searching for a selected pattern of distances having specified colors  
associated with the typographical feature.

17 12. A method as defined in claim 7, wherein the high contrast boundary is between  
a blue pixel sub-component and a green pixel sub-component, the blue pixel sub-component

being interior to a character defined by the image data and the green pixel sub-component being exterior to the character.

18 13. A method as defined in claim 7, wherein the high contrast boundary is between a red pixel sub-component and a green pixel sub-component, the red pixel sub-component being exterior to a character defined by the image data and the green pixel sub-component being interior to the character.

19 14. A method as defined in claim 7, further comprising mapping spatially different sets of one or more samples of the image data to individual pixel sub-components of the pixels rather than mapping samples to entire pixels.

20 15. A method as recited in claim 1, wherein the elements include one or more control points and the image data is associated with a character, wherein hinting the image data comprises:

analyzing the image data associated with the character, the image data defining:

an outline of the character using at least the one or more control points;

distances between key control points; and

a parent/child relationship of the key control points;

identifying distances of the character that are indicative of typographical features of the character to be positioned on high contrast boundaries, the identified distances being associated with at least some of the key control points; and

positioning the identified key control points of the character to grid points on the grid that correspond to high contrast boundaries of pixel sub-components on the display device.

21 16. A method as defined in claim 15, wherein the distances include black distances which are interior to the outline of the character, white distances that are exterior to the outline of the character and grey distances which are a combination of black and white distances.

22 17. A method as defined in claim 15, wherein the distances define a stem width identified by the at least some of the key control points.

23 18. A method as defined in claim 17, further comprising positioning the stems of the character.

24 19. A method as defined in claim 15, wherein the high contrast boundary is between blue pixel sub-components and green pixel sub-components, the blue pixel sub-components being interior to the character and the green pixel sub-components being exterior to the character.

25 20. A method as defined in claim 15, wherein the high contrast boundary is between red pixel sub-components and green pixel sub-components, the red pixel sub-components being exterior to the character and the green pixel sub-components being interior to the character.

26 21. A method as defined in claim 15, further comprising positioning the left character edge on the boundaries.

27 22. A method as defined by claim 1, wherein hinting the image data comprises:  
deriving a parent/child hierarchy representative of certain ones of said selected elements from the image data;  
examining the image data for patterns that indicate typographical features, wherein the patterns are identified by the certain ones of said selected elements and each node of the hierarchy is associated with one of the typographical features; and  
while traversing a data structure representing the hierarchy, phase adjusting one or more selected typographical features by positioning the certain ones of said selected elements associated with the selected typographical features on grid points of the grid that correspond to a high contrast boundary between pixel sub-components, the high contrast boundary not being a boundary between pixels.

28 23. A method as defined in claim 22, further comprising, as successive typographical features are phase adjusted, accounting for an error introduced from phase adjusting the previous typographical feature.

29 24. A method as defined in claim 23, wherein the error is equal to the displacement of the previous typographical feature.

30 25. A method as defined in claim 22, wherein the pixel sub-components of the pixels are arranged on the display device to form vertical stripes of same-colored pixel

subcomponents and wherein the one or more selected typographical features include a vertical stem of the character.

31 26. A method as defined in claim 22, wherein the pixel sub-components of the pixels are arranged on the display device to form horizontal stripes of same-colored pixel subcomponents and wherein the one or more selected typographical features include a horizontal segment of the character.

32 27. A method as defined in claim 22, wherein the patterns include alternating black and white distances, wherein the black distances include dimensions that are interior to the character and the white distances include dimensions that are exterior to the character.

33 28. A method as defined in claim 22, wherein the patterns include alternating black and grey distances, wherein the black distances include dimensions that are interior to the character and wherein the grey distances include dimensions that are both interior and exterior to the character.

WORKMAN, NYDEGGER & SEELEY  
A PROFESSIONAL CORPORATION  
ATTORNEYS AT LAW  
1000 EAGLE GATE TOWER  
60 EAST SOUTH TEMPLE  
SALT LAKE CITY, UTAH 84111

34<sup>29</sup>. A computer program product for implementing, in a computer system having a display device for displaying an image, the display device having a plurality of pixels, each pixel including a plurality of pixel sub-components, a method for hinting the image data in preparation for displaying the image data on the display device, the computer program product comprising:

a computer readable medium carrying computer executable instructions for implementing the method, the computer executable instructions, when executed, performing:

grid fitting the image data to grid points of a grid that corresponds to the pixels and pixel sub-components of the display device such that one or more elements defining a typographical feature of the image data correspond to the grid points;

phase adjusting the typographical feature such that the typographical feature coincides with a location of the grid that represents a boundary between pixel sub-components, the boundary being designated as a high contrast boundary due to the color contrast of the sub-pixel components which define the boundary, and which may comprise a boundary other than one which is between pixels; and

interpolating the image data such that the position on the grid of remaining elements of the image data is adjusted.

35 30. A computer program product of claim 29, wherein the image data represents a character and, the method further comprising:



identifying selected points of the image data by examining dimensions and distances stored and associated with the image data; and

based on the examined dimensions and distances, recognizing the selected points as defining the typographical feature that is to be phase adjusted.

36 31. A computer program product as defined in claim 29, wherein the pixel sub-components are arranged on the display device to form vertical stripes of same-colored pixel sub-components, and wherein the typographical feature is a character stem that is parallel to the direction of the vertical stripes.

37 32. A computer program product as defined in claim 29, wherein the method further comprises mapping spatially different sets of one or more samples to each of the pixel sub-components of a selected pixel, as opposed to mapping one or more samples to the entire selected pixel.

38 33. A computer program product as defined in claim 32, wherein the method further comprises displaying the image on the display device based on the image data, resulting in the typographical feature being displayed at the high contrast boundary.

39 34. A computer program product as defined in claim 33, wherein displaying the image on the display device comprises separately controlling each of the pixel sub-components of the selected pixel by applying to the each of pixel sub-components of the selected pixel a luminance intensity value generated from the spatially different set of one or more samples mapped to the particular pixel sub-component.

40<sup>35</sup>. A computer program product for implementing, in a computer system having a display device for displaying an image, the display device having a plurality of pixels, each pixel including a plurality of pixel sub-components, a method for hinting the image data in preparation for displaying the image data on the display device, the computer program product comprising:

a computer readable medium carrying computer executable instructions for implementing the method, the computer executable instructions, when executed, performing:

obtaining image data having selected elements with positions relative to the grid, the positions of at least one of the selected elements of the obtained image data not coinciding with a boundary between pixel sub-components;

hinting the image data such that a typographical feature defined by one or more of the selected elements is adjusted to a position on the grid that corresponds to a selected boundary between pixel sub-components, the selected boundary being designated as a high contrast boundary due to the color contrast of the subpixel components which define the boundary other than a boundary between pixels; and

displaying the image on the display device using the image data, the typographical feature being displayed at the high contrast boundary.

4|36. In a computer system having a processor and a display device having a plurality of pixels for displaying image data, each pixel having a plurality of pixel sub-components, a method for hinting the image data, the method comprising:

grid fitting the image data to grid points of a grid that corresponds to the pixels and pixel sub-components of the display device such that one or more elements defining a typographical feature of the image data correspond to the grid points;

phase adjusting the typographical feature such that the typographical feature coincides with a location of the grid that represents a boundary between pixel sub-components, the boundary being designated as a high contrast boundary, wherein phase adjusting comprises:

analyzing hinting instructions associated with the image data for patterns that are indicative of the typographical feature;

deriving, from the hinting instructions, a directed acyclic graph, wherein the topology of the typographical feature is at least partially defined by one or more nodes of the directed acyclic graph; and

based on a traversal of the directed acyclic graph, identifying the position of the typographical feature and repositioning the typographical feature to the high contrast boundary; and

interpolating the image data such that the position on the grid of remaining elements of the image data is adjusted.

42|37. A method as recited in claim 36, further comprising:  
traversing the directed acyclic graph; and

encountering a node that corresponds to a point of the image data that is to be repositioned on the grid; and

accounting for an error introduced by a repositioning of a point corresponding to a previous node of the directed acyclic graph.

4338. A method as defined in claim 36, wherein analyzing the hinting instructions further comprises searching for a selected pattern of distances having specified colors associated with the typographical feature.

WORKMAN, NYDEGGER & SEELEY  
A PROFESSIONAL CORPORATION  
ATTORNEYS AT LAW  
1000 EAGLE GATE TOWER  
60 EAST SOUTH TEMPLE  
SALT LAKE CITY, UTAH 84111